

United States Patent and Trademark Office



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO |
|---|-----------------|----------------------|-------------------------|-----------------|
| 09/976,604 | 10/12/2001 | Mark D. Penk | A-6727 | 3301 |
| 5642 | 7590 07/01/2005 | | EXAM | INER |
| SCIENTIFIC-ATLANTA, INC. | | | ENGLAND, DAVID E | |
| INTELLECTUAL PROPERTY DEPARTMENT 5030 SUGARLOAF PARKWAY | | | ART UNIT | PAPER NUMBER |
| | VILLE, GA 30044 | | 2143 | |
| | | | DATE MAIL ED: 07/01/200 | • |

Please find below and/or attached an Office communication concerning this application or proceeding.

| · | 09/976,604 | PENK ET AL. |
|---|---|--|
| Office Action Summary | Examiner | Art Unit |
| | David E. England | 2143 |
| The MAILING DATE of this communication | | |
| Period for Reply | | |
| A SHORTENED STATUTORY PERIOD FOR RITHE MAILING DATE OF THIS COMMUNICATION - Extensions of time may be available under the provisions of 37 CI after SIX (6) MONTHS from the mailing date of this communication - If the period for reply specified above is less than thirty (30) days, - If NO period for reply is specified above, the maximum statutory period for reply within the set or extended period for reply will, by saying reply received by the Office later than three months after the earned patent term adjustment. See 37 CFR 1.704(b). | ON. FR 1.136(a). In no event, however, may a son. a reply within the statutory minimum of the period will apply and will expire SIX (6) MO statute, cause the application to become A | reply be timely filed irty (30) days will be considered timely. NTHS from the mailing date of this communication BANDONED (35 U.S.C. § 133). |
| Status | | |
| 1) Responsive to communication(s) filed on | 18 March 2005. | |
| | This action is non-final. | |
| 3) Since this application is in condition for all | | tters, prosecution as to the merits is |
| closed in accordance with the practice und | der <i>Ex parte Quayle</i> , 1935 C.I | D. 11, 453 O.G. 213. |
| Disposition of Claims | | |
| 4)⊠ Claim(s) <u>1-43</u> is/are pending in the applica | ation. | |
| 4a) Of the above claim(s) is/are with | | |
| 5) Claim(s) is/are allowed. | | |
| 6)⊠ Claim(s) <u>1-43</u> is/are rejected. | | |
| 7) Claim(s) is/are objected to. | • | |
| 8) Claim(s) are subject to restriction a | nd/or election requirement. | |
| Application Papers | | |
| 9) The specification is objected to by the Exa | miner. | |
| 10)⊠ The drawing(s) filed on <u>12 October 2001</u> is | | objected to by the Examiner. |
| Applicant may not request that any objection to | | |
| Replacement drawing sheet(s) including the co | = . | i i i |
| 11)☐ The oath or declaration is objected to by th | ne Examiner. Note the attache | ed Office Action or form PTO-152. |
| Priority under 35 U.S.C. § 119 | | • |
| 12) Acknowledgment is made of a claim for for | reign priority under 35 U.S.C. | & 119(a)-(d) or (f) |
| a) ☐ All b) ☐ Some * c) ☐ None of: | engin priority under 00 0.0.0. | 3 (() () () () . |
| 1.☐ Certified copies of the priority docur | nents have been received. | |
| 2. Certified copies of the priority docur | • | Application No |
| 3. Copies of the certified copies of the | | · · · |
| application from the International Bu | ureau (PCT Rule 17.2(a)). | |
| * See the attached detailed Office action for a | a list of the certified copies no | t received. |
| | | |
| Attachment(s) | | |
| 1) Notice of References Cited (PTO-892) | 4) Interview | Summary (PTO-413) |
| 2) Notice of Draftsperson's Patent Drawing Review (PTO-948 | B) Paper No | (s)/Mail Date |
| Information Disclosure Statement(s) (PTO-1449 or PTO/S Paper No(s)/Mail Date | B/08) 5) Notice of 6) Other: | Informal Patent Application (PTO-152) |
| | | |

1. Claims 1-43 are presented for examination.

Drawings

- 2. The drawings are objected to under 37 CFR 1.83(a). The drawings must show every feature of the invention specified in the claims. Therefore, the "grouping multiple devices of the plurality of devices into a plurality of tiers within the digital network" must be shown or the feature(s) canceled from the claim(s). No new matter should be entered.
- The drawings are objected to under 37 CFR 1.83(a). The drawings must show every feature of the invention specified in the claims. Therefore, the "determining whether the first plurality of devices is the same as the second plurality of devices; and responsive to determining the first plurality of devices is not the same as the second plurality of devices, generating an alert message." must be shown or the feature(s) canceled from the claim(s). No new matter should be entered.

Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. The figure or figure number of an amended drawing should not be labeled as "amended." If a drawing figure is to be canceled, the appropriate figure

Art Unit: 2143

Page 3

must be removed from the replacement sheet, and where necessary, the remaining figures must be renumbered and appropriate changes made to the brief description of the several views of the drawings for consistency. Additional replacement sheets may be necessary to show the renumbering of the remaining figures. The replacement sheet(s) should be labeled "Replacement Sheet" in the page header (as per 37 CFR 1.84(c)) so as not to obstruct any portion of the drawing figures. If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

Claim Rejections - 35 USC § 102

4. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 5. Claims 1 8, 20, 21, 33 36 and 39 43 are rejected under 35 U.S.C. 102(e) as being anticipated by Teraoka U.S. Patent No. 6292836.
- 6. Referencing claim 33, as closely interpreted by the Examiner, Teraoka teaches an apparatus in a digital network that receives a transport stream, the apparatus comprising:

- 7. a port adapted to receive the transport stream, wherein the transport stream has a transport stream identifier associated therewith, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D"); and
- 8. a processor in communication with the input port, the processor adapted to monitor the transport stream identifier and respond to changes thereto by generating a network message, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D").
- 9. Referencing claim 34, as closely interpreted by the Examiner, Teraoka teaches the network message includes a second transport stream identifier, wherein the second transport stream identifier is the new transport stream identifier associated with the received transport stream, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D").
- 10. Referencing claim 35, as closely interpreted by the Examiner, Teraoka teaches the network message further includes a device identifier associated with the apparatus, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D").
- 11. Referencing claim 36, as closely interpreted by the Examiner, Teraoka teaches the network message is transmitted through the port, (e.g. col. 5, lines 1 11).

Referencing claim 39, as closely interpreted by the Examiner, Teraoka teaches a transmitter in communication with the processors the transmitter adapted to transmit a second transport stream that includes at least a portion of the received transport stream, (e.g. col. 6, lines 20-35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54-col. 7, line 8, "VIP address of computer C=VIPaddr C, IP address of computer C=IPaddr D"); and

- a second port adapted to receive and transmit messages, wherein the network message is transmitted through the second port, and the network message includes a device identifier associated with the apparatus, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D").
- 14. Referencing claim 40, as closely interpreted by the Examiner, Teraoka teaches the network message includes the current transport stream identifier associated with the received transport stream, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D").
- 15. Referencing claim 41, as closely interpreted by the Examiner, Teraoka teaches the second transport stream has a second transport stream identifier associated therewith, and the processor receives a remapping message from the second port and responds thereto by remapping the second transport stream identifier associated with the second transport stream, (e.g. col. 6, lines

20 – 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 – col. 7, line 8, "VIP address of computer C=VIPaddr C, IP address of computer C=IPaddr D").

- Referencing claim 42, as closely interpreted by the Examiner, Teraoka teaches the processor receives an initiate mapping message from the second port and responds thereto by sending through the second port a network message having a device identifier associated with the apparatus and the transport stream identifier included therein, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr C, IP address of computer C=IPaddr D").
- 17. Referencing claim 43, as closely interpreted by the Examiner, Teraoka teaches the processor receives an initiate mapping message from the port and responds thereto by sending through the port a network message having a device identifier associated with the apparatus and the transport stream identifier included therein, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D").
- 18. Referencing claim 20, as closely interpreted by the Examiner, Teraoka teaches digital network further includes a plurality of transport stream receivers, which receive at least one transport stream, and further including the step of:
- 19. receiving a message from multiple transport stream receivers of the plurality of transport stream receivers, each message per receiver including a device identifier and a transport stream

Application/Control Number: 09/976,604 Page 7

Art Unit: 2143

identifier, which is associated with a transport stream received by the transport stream receiver, (e.g. col. 6, lines 20 – 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 – col. 7, line 8, "VIP address of computer C=VIPaddr C, IP address of computer C=IPaddr D").

- 20. Referencing claim 21, as closely interpreted by the Examiner, Teraoka teaches each of the multiple transport stream receivers respond to and initiate mapping message by sending the message, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D").
- 21. Claims 1 8 are rejected for similar reasons as stated above.

Claim Rejections - 35 USC § 103

- 22. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 23. Claim 9 is rejected under 35 U.S.C. 103(a) as being unpatentable over by Rao (6789118) in view of Teraoka (6292836).

- 24. Referencing claim 9, as closely interpreted by the Examiner, Rao teaches a method of mapping a digital network that includes a plurality of devices that receive and transmit at least one transport stream, the method comprising the steps of:
- 25. grouping multiple devices of the plurality of devices into a plurality of tiers within the digital network, (e.g. col. 20, lines 24 40); and
- associating a first particular device of a first tier with a second particular device of a second tier of the digital network, wherein the second particular device receives a transport stream transmitted from the first particular device, (e.g. col. 20, lines 41 63), but does not specifically teach a transport stream with a transport stream ID. Teraoka teaches a transport stream with a transport stream ID, (e.g., col. 1, lines 29 55 & col. 6, lines 20 35). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Teraoka with Rao because utilizing a type of stream ID could aid in the differentiation between packets that traverse a router. Furthermore, it may also be used in case a packet is missing from transmission. If a packet is out of sequence then the correct sequence number that is attached to the packet will differentiate it from other packets.
- 27. Claim 10 is rejected under 35 U.S.C. 103(a) as being unpatentable over Rao (6789118) in view of Brandt et al. (6377993) (hereinafter Brandt).
- As per claim 10, as closely interpreted by the Examiner, Rao teaches a method of mapping a digital network that includes a plurality of devices that receive and transmit at least one transport stream, the method comprising the steps of:

Art Unit: 2143

29. grouping multiple devices of the plurality of devices into a plurality of tiers within the digital network, (e.g. col. 20, lines 24 - 40); and

Page 9

- 30. associating a first particular device of a first tier with a second particular device of a second tier of the digital network, wherein the second particular device receives a transport stream transmitted from the first particular device, (e.g. col. 20, lines 41 63), but does not specifically teach the plurality of tiers including a source tier, an intermediate tier, and an output tier. Brandt teaches the plurality of tiers including a source tier, an intermediate tier, and an output tier, (e.g., col. 6, lines 18 39). It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine Brandt with Rao because providing an intermediate tier could provide a secure web server and back end services to provide applications that establish user sessions, govern user authentication and their entitlements, and communicate with adaptor programs to simplify the interchange of data across the network.
- 31. Claims 11 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rao and Teraoka as applied to claim 9 above, and in further view of Hegde (6570875).
- 32. As per claim 11, as closely interpreted by the Examiner, Rao and Teraoka do not specifically teach prior to the step of grouping, further including the steps of:
- 33. transmitting an initiate mapping message to the plurality of devices; and
- 34. receiving a network message from the plurality of devices, each network message per device including an output transport stream identifier and a device identifier, wherein the

transport stream identifier is associated with a transport stream transmitted by a device associated with the device identifier.

- 35. Hegde teaches prior to the step of grouping, further including the steps of:
- transmitting an initiate mapping message to the plurality of devices, (e.g. col. 8, lines 7 36. 17); and
- 37. receiving a network message from the plurality of devices, each network message per device including an output transport stream identifier and a device identifier, wherein the transport stream identifier is associated with a transport stream transmitted by a device associated with the device identifier, (e.g. col. 8, lines 18 – 32). It would have been obvious to one of ordinary skill in the art at the time the invention was conceived to combine Hegde with the combine system of Rao and Teraoka because it would be more efficient for a system to set up links, port id and addresses to different groups when the system is powered on so updated information that is on the system can be transmitted to the device to ensure that any changes in the network are propagated throughout the network to ensure timely transmission of newly installed devices or transmitted information.
- 38. As per claim 12, as closely interpreted by the Examiner, Rao and Teraoka do not specifically teach the step of grouping further includes the step of:
- 39. using the device identifier included in each of the network messages and a table to group the plurality of devices into tiers.
- 40. Hegde teaches the step of grouping further includes the step of:

- 41. using the device identifier included in each of the network messages and a table to group the plurality of devices into tiers, (e.g. col. 7, lines 15 26). It would have been obvious to one of ordinary skill in the art at the time the invention was conceived to combine Hegde with the combine system of Rao and Tokuyo because of similar reasons stated above. Furthermore, if there were a group of permanent users it would be advantageous to store the group of users in a table so to reference them if needed in a multicast transmission circumstance.
- 42. As per claim 13, as closely interpreted by the Examiner, Rao each of the network messages further includes an input network stream identifier associated with a second transport stream, which is received by a device associated with the device identifier, (e.g. col. 20, lines 41 59).
- 43. As per claim 14, as closely interpreted by the Examiner, Rao the input network stream identifier includes a network transport stream source indicator, (e.g. col. 20, lines 41 59).
- As per claim 15, as closely interpreted by the Examiner, Rao the network transport stream source indicator is a predetermined value for a device that is a source of a network transport stream in the digital network, (e.g. col. 20, lines 41 59).
- As per claim 16, as closely interpreted by the Examiner, Rao and Hegde do not specifically teach determining whether a particular transport stream identifier associated with a particular transport stream transmitted from a particular device of the multiple devices of a given

tier is the same as one or more transport stream identifiers associated with other transport streams transmitted from one or more devices of the multiple devices of the given tier;

- 46. responsive to determining the particular transport stream identifier is not the same, associating the particular device with the particular transport stream identifier;
- 47. responsive to determining the particular transport stream identifier is the same, further including the steps of:
- 48. determining a new transport stream identifier for the particular transport stream, wherein the new transport stream identifier is different from other transport stream identifiers associated with transport streams transmitted from the multiple devices of the given tier;
- 49. transmitting a remap message to the particular device, wherein the particular device responds thereto by remapping the particular transport stream identifier associated with the particular transport stream to the new transport stream identifier; and
- 50. associating the particular device with the new transport stream identifier.
- Teraoka teaches determining whether a particular transport stream identifier associated with a particular transport stream transmitted from a particular device of the multiple devices of a given tier is the same as one or more transport stream identifiers associated with other transport streams transmitted from one or more devices of the multiple devices of the given tier, (e.g. col. 6, lines 20 35);
- responsive to determining the particular transport stream identifier is not the same, associating the particular device with the particular transport stream identifier, (e.g. col. 6, lines 20-35);

Art Unit: 2143

53. responsive to determining the particular transport stream identifier is the same, further including the steps of:

Page 13

- 54. determining a new transport stream identifier for the particular transport stream, wherein the new transport stream identifier is different from other transport stream identifiers associated with transport streams transmitted from the multiple devices of the given tier, (e.g. col. 5, line 45 col. 6, line 2);
- transmitting a remap message to the particular device, wherein the particular device responds thereto by remapping the particular transport stream identifier associated with the particular transport stream to the new transport stream identifier, (e.g. col. 6, line 56 col. 7, line 8); and
- associating the particular device with the new transport stream identifier, (e.g. col. 6, line 56 col. 7, line 8). It would have been obvious to one of ordinary skill in the art at the time the invention was conceived to combine Teraoka with the combine systems of Rao and Hegde because remapping a message with a different transport stream identifier would ensure that no duplications in identifiers are given out to different system. Doing so would aid in misstransmission of information to devices that did not request said information.
- 57. As per claim 17, as closely interpreted by the Examiner, Rao and Hegde do not specifically teach after the step of transmitting the remap message, further including the step of:
- 58. receiving another network message from a second particular device, wherein the second particular device receives the particular transport stream transmitted from the first particular

Art Unit: 2143

device. Teraoka teaches after the step of transmitting the remap message, further including the

Page 14

step of:

59. receiving another network message from a second particular device, wherein the second

particular device receives the particular transport stream transmitted from the first particular

device, (e.g. col. 6, line 56 - col. 7, line 8). It would have been obvious to one of ordinary skill in

the art at the time the invention was conceived to combine Teraoka with the combine systems of

Rao and Hegde because it would be more efficient for a system to reestablish communication

with other network devices so the transfer of addresses and port numbers can be propagated

throughout the network.

60. As per claim 18, as closely interpreted by the Examiner, Rao and Hegde do not

specifically teach the second particular device sends the other network message responsive to the

first particular device remapping the particular transport stream identifier associated with the

particular transport stream. Teraoka teaches the second particular device sends the other network

message responsive to the first particular device remapping the particular transport stream

identifier associated with the particular transport stream, (e.g. col. 6, line 56 - col. 7, line 8). It

would have been obvious to one of ordinary skill in the art at the time the invention was

conceived to combine Teraoka with the combine systems of Rao and Hegde because of similar

reasons stated above.

As per claim 19, as closely interpreted by the Examiner, Rao teaches associating the

particular device with at least one input transport stream identifier, wherein the network message

Application/Control Number: 09/976,604 Page 15

Art Unit: 2143

from the particular device includes the at least one transport stream identifier, which is associated with the at least one transport stream received in the particular device, (e.g. col. 20, lines 41 - 59).

- 62. Claims 22 24 are rejected under 35 U.S.C. 103(a) as being unpatentable over Tokuyo et al. (6829238) (hereinafter Tokuyo) in view of Rao (6789118).
- Referencing claim 22, as closely interpreted by the Examiner, Tokuyo teaches a method of mapping a digital network, the method comprising:
- assigning a unique transport stream identifier to each transport stream of a plurality of transport streams, wherein the plurality of transport streams are transmitted from a plurality of devices included in the digital network, (e.g. col. 4, lines 15 37, "...assigns a unique identification number to the TCP..." & col. 6, lines 5 26, "IP packet, source and destination IP address, port number, unique identification number");
- associating each assigned unique transport stream identifier with a particular device of the plurality of devices, wherein the particular device transmits the transport stream having the unique transport stream identifier assigned thereto, (e.g. col. 4, lines 15 37, "...assigns a unique identification number to the TCP..." & col. 6, lines 5 26, "IP packet, source and destination IP address, port number, unique identification number");
- 66. transmitting to each device of the plurality each assigned unique transport stream identifier associated therewith, (e.g. col. 4, lines 15 37, "...assigns a unique identification

number to the TCP..." & col. 6, lines 5 – 26, "IP packet, source and destination IP address, port number, unique identification number");

- 67. receiving a network message from multiple devices of the plurality of devices, each network message including at least one input transport stream identifier, (e.g. col. 6, lines 5 26, "IP packet, source and destination IP address, port number, unique identification number"); but does not specifically teach using the multiple network messages to determine a hierarchy of devices for the plurality devices.
- Rao teaches using the multiple network messages to determine a hierarchy of devices for the plurality devices, (e.g. col. 16, lines 24 48, "User 1 has QoA level of one, User 2 has a QoA level of two, and User 3 has a QoA level of three."). It would have been obvious to one of ordinary skill in the art at the time the invention was conceived to combine Rao with Tokuyo because it would be more efficient for the higher level users that system's assigned QoA be serviced first so there higher level information can be processed in a timely manner.
- As per claim 23, as closely interpreted by the Examiner, Tokuyo teaches the at least one input transport stream identifier is one of the unique transport stream identifiers, (e.g. col. 4, lines 15 37, "...assigns a unique identification number to the TCP..." & col. 6, lines 5 26, "IP packet, source and destination IP address, port number, unique identification number").
- As per claim 23, as closely interpreted by the Examiner, Tokuyo teaches the step of using the multiple network messages further includes the step of:

- associating a first device of the plurality of devices with a second device of the multiple devices, wherein the at least one input transport stream identifier of the network message from the second device includes at least one unique transport stream identifier associated with the first device, (e.g. col. 7, line 59 4, "src-IP, src-port number, dst-IP, dst-port number" & col. 8, lines 34 49).
- 72. Claims 25 32 are rejected under 35 U.S.C. 103(a) as being unpatentable over Tokuyo and Rao as applied to claim 22 above, and in further view of Teraoka (6292836).
- As per claim 25, as closely interpreted by the Examiner, Tokuyo and Rao do not specifically teach prior to the step of assigning, receiving a second network message from the plurality of devices, each second network message per device including an output transport stream identifier. Teraoka teaches prior to the step of assigning, receiving a second network message from the plurality of devices, each second network message per device including an output transport stream identifier, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D"). It would have been obvious to one of ordinary skill in the art at the time the invention was conceived to combine Teraoka with the combine system of Tokuyo and Rao because it would be more convenient for a first device in a network to have the ability to move from one location to another while continual connection with a second device that the first device was communicating with, while having this process be transparent to both users.

Page 18

- 74. As per claim 26, as closely interpreted by the Examiner, Tokuyo and Rao do not specifically teach the step of assigning further includes the step of:
- 75. using the output transport stream identifier included in each second network message from the plurality of devices to assign the unique transport stream identifier.
- 76. Teraoka teaches the step of assigning further includes the step of:
- 177. using the output transport stream identifier included in each second network message from the plurality of devices to assign the unique transport stream identifier, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D"). It would have been obvious to one of ordinary skill in the art at the time the invention was conceived to combine Teraoka with the combine system of Tokuyo and Rao because of similar reasons stated above.
- As per claim 27, as closely interpreted by the Examiner, Tokuyo teaches sending a mapping initiation message to a second plurality of devices included in the digital network, wherein the second plurality of devices includes the first plurality of devices, and each of the first plurality of devices respond to the mapping initiation message by sending the second network message, (e.g. col. 4, lines 15 37, "...assigns a unique identification number to the TCP..." & col. 6, lines 5 26, "IP packet, source and destination IP address, port number, unique identification number"), but does not specifically teach prior to the step of receiving the second network message, (e.g. col. 6, lines 20 35, "VendPointAddr-B={VIP_C, port_C}" & col. 6, line 54 col. 7, line 8, "VIP address of computer C=VIPaddr_C, IP address of computer C=IPaddr_D"). It would have been obvious to one of ordinary skill in the art at the time the

invention was conceived to combine Teraoka with the combine system of Tokuyo and Rao because it would be more efficient for a system to have a layout of the system it would be traversing in the network so the information that is being sent is received at it's destination with the least hops and/or failures encountered.

- 79. As per claim 28, as closely interpreted by the Examiner, Tokuyo does not specifically teach determining whether the first plurality of devices is the same as the second plurality of devices; and
- 80. responsive to determining the first plurality of devices is not the same as the second plurality of devices, generating an alert message.
- Rao teaches determining whether the first plurality of devices is the same as the second plurality of devices, (e.g. col. 20, lines 41 59); and
- 82. responsive to determining the first plurality of devices is not the same as the second plurality of devices, generating an alert message, (e.g. col. 20, lines 3 13 & 41 59). It would have been obvious to one of ordinary skill in the art at the time the invention was conceived to combine Teraoka with the combine system of Tokuyo and Rao because it would be more secure if the system only gave specific access and privileges to users of a specific network. Also in doing so could block out potential invaders to a system.
- 83. Claims 29 32 are rejected for similar reasons as stated above.

- 84. Claims 37 and 38 are rejected under 35 U.S.C. 103(a) as being unpatentable over Teraoka as applied to claim 33 above, and in view of Rao (6789118).
- 85. As per claim 37, as closely interpreted by the Examiner, Teraoka does not specifically teach the port is a plurality of input ports, each input port of the plurality of input ports receiving at least one transport stream having a transport stream identifier associated therewith, and the processor is adapted to monitor the transport stream identifier of each input transport stream and respond to changes thereto by generating the network message.
- 86. Rao teaches the port is a plurality of input ports, each input port of the plurality of input ports receiving at least one transport stream having a transport stream identifier associated therewith, and the processor is adapted to monitor the transport stream identifier of each input transport stream and respond to changes thereto by generating the network message, (e.g. col. 24, lines 18 34). It would have been obvious to one of ordinary skill in the art at the time the invention was conceived to combine Rao with Teraoka because if ports have the same identification number, errors in a system would occur because of the systems inability to differentiating between a plurality of ports in a system. Assigning a plurality of ports different identification numbers would make for a more efficient system that does not encounter errors because of similar port identification numbers.
- 87. As per claim 38, as closely interpreted by the Examiner, Teraoka teaches the network message includes the current transport stream identifier associated with each of the received input transport streams, (e.g. col. 6, lines 20 35).

Page 21

Application/Control Number: 09/976,604

Art Unit: 2143

Response to Arguments

- 88. Applicant's arguments filed 3/18/2005 have been fully considered but they are not persuasive.
- 89. In the Remarks, Applicant argues in substance that the limitation of, "grouping multiple devices of the plurality of devices into a plurality of tiers within the digital network," can be found in Fig. 4 where it clearly shows one example of multiple devices grouped into a plurality of tiers.
- 90. As to part 1, Examiner agrees with Applicant in stating that Fig. 4 clearly shows one example of multiple devices grouped into a plurality of tiers, but that is not the limitations. The limitation described above states the act of "grouping" multiple devices of the plurality o9f devices into a plurality of tiers. Fig. 4 only shows devices already grouped. There are no tree diagrams that show the act of "grouping" multiple devices.
- 91. In the Remarks, Applicant argues in substance that the limitation of, "determining whether the first plurality of devices is the same as the second plurality of devices; and responsive to determining the first plurality of devices is not the same as the second plurality of devices, generating an alert message," can be found in Fig. 7B and accompanying specification on page 18, lines 15 23 and page 24, line 32 page 25, line 2.

Art Unit: 2143

92. As to part 2, Examiner agrees with Applicant that the specification teaches the limitation described above, yet Fig. 7B does not show an "alert message being generated" nor a determining step as to "whether the first plurality of devices is the same as the second plurality of devices".

Page 22

- 93. In the Remarks, Applicant argues in substance that an IP address as taught in Teraoka is not a transport stream identifier (TSID) The TSID identifies a particular stream of data It does not identify a device. A device with one IP address may be a source or destination for several transport streams. Teraoka does disclose identifying a particular stream of data. Additionally, Teraoka does not disclose a processor at the input port that generates a message.
- As to part 3, Examiner agrees with Applicant in that <u>Teraoka does disclose identifying a particular stream of data</u>. This is apparent in the above rejection as restated for the Applicant above. In response to applicant's argument that the references fail to show certain features of applicant's invention, it is noted that the features upon which applicant relies (i.e., *input port*) are not recited in the rejected claim(s). Although the claims are interpreted in light of the specification, limitations from the specification are not read into the claims. See *In re Van Geuns*, 988 F.2d 1181, 26 USPQ2d 1057 (Fed. Cir. 1993). Examiner would like to point to the Amended section of claim 33 which is amended to take out the term *input* so to only state a port.
- 95. In the Remarks, Applicant argues in substance that Applicant respectfully submit that claim 1 contains elements not present in claims 20, 21, 33 36 and 39 43, and a rejection of claims 1 8 for similar reasons as claims 20, 21, 33 36 and 39 43 is improper For instance,

none of claims 20, 21, 33 - 36 and 39 - 43 recite a controller adapted to generate a transport stream map. Therefore, a rejection of claims 1 - 8 for similar reasons as claims 20, 21, 33 - 36 and 39 - 43 is improper and the rejection should be withdrawn.

- As to part 4, Examiner would like to draw the Applicant's attention to the cited areas of the Prior art of record. There are numerous references to devices that generate IP addresses, source and destination, which map out a path for packets to travel and traverses a router, which could be interpreted as a controller. Therefore, one of ordinary skill in the art would know that this could be interpreted as transport stream map. Examiner would also like to point out that nowhere in the broad claim language is it stated that the transport stream map could be something specifically different, which leaves one to interpret the claims as broadly as possible.
- 97. In the Remarks, Applicant argues in substance that independent claim 22 is allowable for at least the reason that none of Tokuyo, Rao, or Teraoka disclose, teach, or suggest at least assigning a unique transport stream identifier to each transport stream of a plurality of transport streams. Tokuyo discloses a TCP connection ID. A TCP connection ID identifies a connection between two devices. However, this does not disclose assigning identifiers to individual transport streams. Neither Rao nor Teraoka corrects this omission.
- 98. As to part 5, Examiner would like to draw the Applicant's attention to the prior art of Tokuyo, in which, not only does Tokuyo teach a TCP connection ID that is uniquely assigned to each connection that is in the stream or packets that are transmitted. The broad claim language states that assigning a unique transport stream identifier to each transport stream of a plurality of transport streams, wherein the plurality of transport streams are transmitted from a plurality of

Art Unit: 2143

devices included in the digital network. This could be interpreted as each device sends a stream or packet and that each device connection is its own unique connection to another device and that no two devices can have the same address as is well known in the art. Therefore, if each pair of devices make a connection and each address is unique in the digital network and each device sends one stream or packet in the plurality of devices, then the "unique identification number" that is associated with the pair of devices in the connection can act as a type of transport stream identifier, (e.g., cols. 7 – 8 and described in above rejection).

Page 24

- 99. In the Remarks, Applicant argues in substance that because independent claim 33 is allowable over the cited art of record dependent claims 37 and 38 are allowable as a matter of law for at least the reason that dependent claims 37 and 38 contain all the steps/features of independent claim 33.
- As to part 6, Examiner would like to draw the Applicant's attention to the above responses to remarks for they apply to this remark as well.
- Applicant's arguments with respect to claims 9 and 10 have been considered but are moot 101. in view of the new ground(s) of rejection from limitations, "wherein the second particular device receives a transport stream with a transport stream ID transmitted from the first particular device," and "the plurality of tiers including a source tier, an intermediate tier, and an output tier."

Conclusion

102. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to David E. England whose telephone number is 571-272-3912. The examiner can normally be reached on Mon-Thur, 7:00-5:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David A. Wiley can be reached on 571-272-3923. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Art Unit: 2143

Page 26

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

David E. England Examiner Art Unit 2143

De ///

WILLIAM C. VAUGHN, JR. PRIMARY EXAMINER

27 June 05